

## MODEL C02-2000

CALENDER used for:

- Transfer printing
- Direct inks reactivation
- Thermosetting - heatsetting

### 1. CHARACTERISTICS OF PRINTING CYLINDER:

- 1.1. Diameter : 200 mm (7,87").
- 1.2. Width : 2.000 mm (78,74").
- 1.3. Working width: 1.800 mm (70,87").

### 2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated by an electronic card with tolerance. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

### 3. TENSION CONTROLS:

- 3.1. Tension control for printing material:
  - Entry: brake with manual adjustment and manual textile tensioner
  - Exit: tangential winding on felt
- 3.2. Tension control for printing paper:
  - Entry: disk brake with pneumatic adjustment.
  - Exit: winding with pneumatic device
- 3.3. Tension control for protection paper:
  - Entry: disk brake with pneumatic adjustment.
  - Exit: tangential winding on felt

### 4. OTHER DEVICES INTO MACHINE:

- 4.1. Single motor
- 4.2. NOMEX felt with pneumatic tension adjustment system and automatic felt-centring device
- 4.3. Incorporated system of felt protection in case of black out and/or compressed air lack
- 4.4. Meter-counter, with alarm to predetermine the length of production runs
- 4.5. General management of the machine, including temperature control by adjustable PLC for the memorization of production data
- 4.6. Front touch-screen keyboard for production data access and programming

### 5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 250 mm (10").
- Fabric roll diameter in exit 250 mm (10").
- Printing paper roll diameter in entry 250 mm (10") - Larger diameters on request.
- Printing paper roll diameter in exit 200 mm (8") - Larger diameters on request.
- Protection paper roll diameter in entry 250 mm (10").
- Protection paper roll diameter in exit 250 mm (10").

### 6. TECHNICAL DATA:

- 6.1. Installed power: 14 kW
- 6.2. Average electric consumption: 9 kW/h

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

## MODEL C02-2000

- 6.3. Compressed air pressure: 3-8 bar
- 6.4. Mechanic speed: 0.1 - 1.7 m/min
- 6.5. Overall dimensions: width 3.100 mm (122,04"). length 1.275 mm (50,20") height 1.485 mm (58,46").
- 6.6. Net weight: 1000 kg
- 6.7. Machine produced according to CE rules
- 6.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

INNOVATION  
SPEED  
FLEXIBILITY  
PROJECT&DESIGN  
INSTALLATION AND ASSISTANCE



Monti Antonio S.p.A.  
Head Office: via dell'Electronica n°5, 36016 Thiene (VI) Italy  
Operation and Administration: via della Fisica n°6, 36016 Thiene (VI) Italy  
T. +39 0445 364619 +39 0445 364707 - sales@montiantonio.com  
[www.montiantonio.com](http://www.montiantonio.com)